

AC Input Modules

D4-08NA AC Input <--->	
Inputs per Module	8
Commons per Module	2 (isolated)
Input Voltage Range	80-265VAC
Peak Voltage	265VAC
AC Frequency	47-63Hz
ON Voltage Level	>70V
OFF Voltage Level	<30V
Input Impedance	12 KΩ
Input Current	8.5mA @ 100VAC 20mA @ 230VAC
Minimum ON Current	5mA
Maximum OFF Current	2mA
Base Power Required 5V	100mA max
OFF to ON Response	5-30ms
ON to OFF Response	10-50ms
Terminal Type (included)	Removable D4-8IOCON
Status Indicators	265VAC Logic side
Weight	8.4oz. (240g)

D4-16NA AC Input <--->	
Inputs per Module	16
Commons per Module	2 (isolated)
Input Voltage Range	80-132VAC
Peak Voltage	132VAC
AC Frequency	47-63Hz
ON Voltage Level	>70V
OFF Voltage Level	<20V
Input Impedance	8KΩ
Input Current	14.5mA @ 120VAC
Minimum ON Current	7mA
Maximum OFF Current	2mA
Base Power Required 5V	150mA max.
OFF to ON Response	5-30ms
ON to OFF Response	10-50ms
Terminal Type (included)	Removable (D4-16IOCON)
Status Indicators	Logic side
Weight	9.5oz. (270g)

See the Terminal Blocks & Wiring Solutions section in this catalog for part numbers of ZIPLink cables and terminal blocks compatible with this module.

